





Millimeter-Wave/Terahertz Uni-/Bi-Directional Filter Development



1 5G/Beyond 5G



2 Uni-directional filter



(((i))) Reflector

Reducing Undesired EM-wave radiation


Extending the spatial coverage of desired EM-wave signals

- 3 Bi-directional filter
- ✓ Transmittance improvement (Desired frequencies)
- ★ Reduction of undesired signal radiation
- ▲ Device / module protection

This work was partly supported by the commissioned research (JPJ012368C07401) by National Institute of Information and Communications Technology (NICT) JSTA-STEP Tryout (JPMJTM22C5), and MIC.SCOPE (JP215003002), Japan.




Absorber (Uni-directional)






For 5G/Beyond 5G EMI/EMC solution


Reflector (Uni-directional)



Radome (Bi-directional)



Target: 100% transmittance, 0% reflectance



Antenna/IC module protection in

electronic devices

Reflected

> wave:0

Incident

wave: 1

Massive amount of

Transmittance improvement

Research for whom?

- Coverage improvement
- Transmittance improvement (For desired frequencies)
- Reducing undesired signal radiation For those interested in achieving these

Research motivation

Radio - wave absobers were needed for improving measurement accuracy at 300 GHz band.

Future Prospects

Wide-band/Multi-functional devices with increasing Operating frequencies